Plywood catalogue by the container.

Furniture, interior and commercial plywood from Ha Hoa, Phu Tho, Vietnam: every face on Eucalyptus, Acacia, Styrax or Pine cores, 3–40 mm, sold by the full 40HC and quoted against a written specification.

Capacity	around 60,000 m³ a year, about 5,000 m³ in an average month
Minimum order	one 40HC; one or two products usual, three to six by agreement
Delivery terms	FOB Hai Phong, CFR or CIF
Held	FSC 100% FSC-C196493 · CARB P2 and TSCA Title VI CARB/EPA 26053 (3–25 mm) · ISO 9001:2015 W2012 · ISO 14001:2015 W2012E · EUDR geolocation for core and face · PPWR packaging test

Faces, cores, sizes

Faces

EV (engineered veneer, white poplar EV in Europe), Poplar and bleached Poplar, Birch (imported face on a Vietnamese core), Okoume, Bintangor, Pine, Eucalyptus, Gurjan, Sapele and others on request. Melamine-, HPL- and paper-overlay-faced panels; UV-ready faces prepared for your own UV line.

Cores

Eucalyptus, Acacia, Styrax or Pine, or combined species laid together to balance price, weight and appearance. No rubberwood core.

Line	Default build	Thickness tolerance
Furniture and interior	A-grade core, stitched, faces sanded and calibrated	±0.3 mm
Commercial	AB core, loose-laid or jointed, unsanded or lightly sanded	±0.5 mm
Packing	AB loose-laid core, usually E2 emission	±0.5–1.0 mm

Thickness and sheet sizes

3, 4, 5, 6, 9, 12, 15, 18, 21, 25, 30 and 40 mm. 3–5 mm panels are always 5 plies; 18 mm usually 11–13 plies. Face veneer 0.2–0.5 mm, usually 0.3 mm for Europe.

Sheet	Used for
1220 × 2440 mm (4 × 8 ft)	The standard export sheet
1220 × 2280 mm	Shorter sheet for furniture parts
1250 × 2500 mm	European format
Cut to size	One sheet split into 4, 6 or 8 panels before packing; custom sizes up to 1250 × 2500 mm

Glue and emission

Glue type and emission class are two separate lines on the order: the default is UF glue at E0 emission, and a melamine-fortified glue for damp rooms usually gives E1. Non-structural LVL for furniture parts, door and frame stock and bed slats is quoted separately.

Truc Mai does not make film-faced, formwork, structural or marine plywood.

Sheets per 40HC: planning table

1220 × 2440 mm, panels only. At most 18 packs on Styrax core, 16 on Acacia and 15 on Eucalyptus, each pack about 1,000 mm high; heavier cores reach the 28,000 kg planning payload first.

Thickness	Styrax core: sheets · m³	Acacia core: sheets · m³	Eucalyptus core: sheets · m³
3 mm	5,994 · 53.5 m³	5,328 · 47.6 m³	4,815 · 43.0 m³
6 mm	2,988 · 53.4 m³	2,656 · 47.4 m³	2,400 · 42.9 m³
9 mm	1,998 · 53.5 m³	1,776 · 47.6 m³	1,605 · 43.0 m³
12 mm	1,494 · 53.4 m³	1,328 · 47.4 m³	1,200 · 42.9 m³
15 mm	1,188 · 53.0 m³	1,056 · 47.2 m³	960 · 42.9 m³
18 mm	990 · 53.0 m³	880 · 47.2 m³	795 · 42.6 m³
25 mm	720 · 53.6 m³	640 · 47.6 m³	570 · 42.4 m³

Sheet counts and weights are planning figures from our packing model, panels only, not a loading record; the carrier and route decide the final payload. Every thickness and the 1250 × 2500 mm sheet are on trucmaiplywood.com/resources/40hc-load-calculator/.

Packing

Plywood is processed wood and outside ISPM 15; solid-wood pallets, battens and dunnage shipped with it fall under ISPM 15.

Certificates, files and terms

Held	Number	Scope
FSC 100% chain of custody	FSC-C196493 · SA-COC-014545	Plywood, Primary Processor; claim on invoice and packing list for products on the current schedule
CARB P2 and TSCA Title VI	CARB/EPA 26053 · TPC-43	Hardwood plywood with veneer core, 3–25 mm, 3–15 plies; 30 and 40 mm are outside the scope
ISO 9001:2015	W2012 · WCERT	Quality management for plywood manufacturing
ISO 14001:2015	W2012E · WCERT	Environmental management system for plywood manufacturing

For EU lots the EUDR file set carries plot geolocation for both the Vietnamese core and the face veneer, so the importer can file its own due-diligence statement. A PPWR test covers the packaging materials.

Documents per shipment

Commercial invoice, packing list, B/L, certificate of origin (EUR.1 for EU-bound lots), phytosanitary and fumigation papers, insurance under CIF, plus the order's certificate files.

Order terms

- Minimum order: one 40HC
- Production: 15–45 days after the 30% deposit, by quantity and agreement
- Payment: 70% against the scanned B/L by T/T, or irrevocable L/C at sight
- Delivery: FOB Hai Phong, CFR or CIF
- Samples: free; new buyers book their own courier, credited against a real order
- Price: quoted per order against the written specification; no price list

Request a quotation

Send application, core, glue and emission, face and back, thickness, sheet size, packing, quantity per month and destination port to contact@trucmaiplywood.com or trucmaiplywood.com/get-a-quotation/.